

# 圧 力 換 算 表

串型ジャッキ  
KST30±15

能 力	押 300 kN	引 300 kN
受圧面積	押 65.30 cm <sup>2</sup>	引 65.30 cm <sup>2</sup>
作動圧力	押 46.00 Mpa	引 46.00 Mpa
ストローク	±150 mm	
質 量	115 kg	

換算: 圧力 (MPa) × 受圧面積 (cm<sup>2</sup>) / 10 = 荷重 (kN)

圧 力	押側荷重	引側荷重
MPa	kN	kN
1.0	7	7
2.0	13	13
3.0	20	20
4.0	26	26
5.0	33	33
6.0	39	39
7.0	46	46
8.0	52	52
9.0	59	59
10.0	65	65
11.0	72	72
12.0	78	78
13.0	85	85
14.0	91	91
15.0	98	98
16.0	104	104
17.0	111	111
18.0	118	118
19.0	124	124
20.0	131	131
21.0	137	137
22.0	144	144
23.0	150	150
24.0	157	157
25.0	163	163

圧 力	押側荷重	引側荷重
MPa	kN	kN
26.0	170	170
27.0	176	176
28.0	183	183
29.0	189	189
30.0	196	196
31.0	202	202
32.0	209	209
33.0	215	215
34.0	222	222
35.0	229	229
36.0	235	235
37.0	242	242
38.0	248	248
39.0	255	255
40.0	261	261
41.0	268	268
42.0	274	274
43.0	281	281
44.0	287	287
45.0	294	294
46.0	300	300

圧 力	押側荷重	引側荷重
MPa	kN	kN