

圧力換算表

押引型ジャッキ RMH50±10

能力	押 500 kN	引 250 kN
受圧面積	押 100.30 cm ²	引 43.50 cm ²
作動圧力	押 50.00 Mpa	引 57.00 Mpa
ストローク	±100 mm	
質量	90 kg	

換算: 圧力 (MPa) × 受圧面積 (cm²) / 10 = 荷重 (kN)

圧力	押側荷重	引側荷重	圧力	押側荷重	引側荷重	圧力	押側荷重	引側荷重
MPa	kN	kN	MPa	kN	kN	MPa	kN	kN
1.0	10	4	26.0	261	113	51.0		222
2.0	20	9	27.0	271	117	52.0		226
3.0	30	13	28.0	281	122	53.0		231
4.0	40	17	29.0	291	126	54.0		235
5.0	50	22	30.0	301	131	55.0		239
6.0	60	26	31.0	311	135	56.0		244
7.0	70	30	32.0	321	139	57.0		250
8.0	80	35	33.0	331	144			
9.0	90	39	34.0	341	148			
10.0	100	44	35.0	351	152			
11.0	110	48	36.0	361	157			
12.0	120	52	37.0	371	161			
13.0	130	57	38.0	381	165			
14.0	140	61	39.0	391	170			
15.0	150	65	40.0	401	174			
16.0	160	70	41.0	411	178			
17.0	171	74	42.0	421	183			
18.0	181	78	43.0	431	187			
19.0	191	83	44.0	441	191			
20.0	201	87	45.0	451	196			
21.0	211	91	46.0	461	200			
22.0	221	96	47.0	471	204			
23.0	231	100	48.0	481	209			
24.0	241	104	49.0	491	213			
25.0	251	109	50.0	500	218			