

压 力 換 算 表

串型ジャッキ  
KST50±30

能 力	押 500 kN	引 500 kN
受圧面積	押 105.80 cm <sup>2</sup>	引 105.80 cm <sup>2</sup>
作動圧力	押 47.00 Mpa	引 47.00 Mpa
ストローク	±300 mm	
質 量	160 kg	

換算: 压力(MPa) × 受压面積(cm<sup>2</sup>)/10 = 荷重(kN)

圧 力	押側荷重	引側荷重
MPa	kN	kN
1.0	11	11
2.0	21	21
3.0	32	32
4.0	42	42
5.0	53	53
6.0	63	63
7.0	74	74
8.0	85	85
9.0	95	95
10.0	106	106
11.0	116	116
12.0	127	127
13.0	138	138
14.0	148	148
15.0	159	159
16.0	169	169
17.0	180	180
18.0	190	190
19.0	201	201
20.0	212	212
21.0	222	222
22.0	233	233
23.0	243	243
24.0	254	254
25.0	265	265

圧 力	押側荷重	引側荷重
MPa	kN	kN
26.0	275	275
27.0	286	286
28.0	296	296
29.0	307	307
30.0	317	317
31.0	328	328
32.0	339	339
33.0	349	349
34.0	360	360
35.0	370	370
36.0	381	381
37.0	391	391
38.0	402	402
39.0	413	413
40.0	423	423
41.0	434	434
42.0	444	444
43.0	455	455
44.0	466	466
45.0	476	476
46.0	487	487
47.0	500	500

[illegible]