

圧力換算表

押引型ジャッキ RMH60±20

能力	押 600 kN	引 600 kN
受圧面積	押 201.10 cm ²	引 88.00 cm ²
作動圧力	押 30.00 Mpa	引 68.00 Mpa
ストローク	±200 mm	
質量	140 kg	

換算: 圧力 (MPa) × 受圧面積 (cm²) / 10 = 荷重 (kN)

圧力	押側荷重	引側荷重
MPa	kN	kN
1.0	20	9
2.0	40	18
3.0	60	26
4.0	80	35
5.0	101	44
6.0	121	53
7.0	141	62
8.0	161	70
9.0	181	79
10.0	201	88
11.0	221	97
12.0	241	106
13.0	261	114
14.0	282	123
15.0	302	132
16.0	322	141
17.0	342	150
18.0	362	158
19.0	382	167
20.0	402	176
21.0	422	185
22.0	442	194
23.0	463	202
24.0	483	211
25.0	503	220

圧力	押側荷重	引側荷重
MPa	kN	kN
26.0	523	229
27.0	543	238
28.0	563	246
29.0	583	255
30.0	600	264
31.0		273
32.0		282
33.0		290
34.0		299
35.0		308
36.0		317
37.0		326
38.0		334
39.0		343
40.0		352
41.0		361
42.0		370
43.0		378
44.0		387
45.0		396
46.0		405
47.0		414
48.0		422
49.0		431
50.0		440

圧力	押側荷重	引側荷重
MPa	kN	kN
51.0		449
52.0		458
53.0		466
54.0		475
55.0		484
56.0		493
57.0		502
58.0		510
59.0		519
60.0		528
61.0		537
62.0		546
63.0		554
64.0		563
65.0		572
66.0		581
67.0		590
68.0		600