

## 圧力換算表

串型ジャッキ  
KST100±20

能力	押 1000 kN	引 1000 kN
受圧面積	押 150.60 cm <sup>2</sup>	引 150.60 cm <sup>2</sup>
作動圧力	押 66.00 Mpa	引 66.00 Mpa
ストローク	±200 mm	
質量	383 kg	

換算: 圧力 (MPa) × 受圧面積 (cm<sup>2</sup>) / 10 = 荷重 (kN)

圧力	押側荷重	引側荷重
MPa	kN	kN
1.0	15	15
2.0	30	30
3.0	45	45
4.0	60	60
5.0	75	75
6.0	90	90
7.0	105	105
8.0	120	120
9.0	136	136
10.0	151	151
11.0	166	166
12.0	181	181
13.0	196	196
14.0	211	211
15.0	226	226
16.0	241	241
17.0	256	256
18.0	271	271
19.0	286	286
20.0	301	301
21.0	316	316
22.0	331	331
23.0	346	346
24.0	361	361
25.0	377	377

圧力	押側荷重	引側荷重
MPa	kN	kN
26.0	392	392
27.0	407	407
28.0	422	422
29.0	437	437
30.0	452	452
31.0	467	467
32.0	482	482
33.0	497	497
34.0	512	512
35.0	527	527
36.0	542	542
37.0	557	557
38.0	572	572
39.0	587	587
40.0	602	602
41.0	617	617
42.0	633	633
43.0	648	648
44.0	663	663
45.0	678	678
46.0	693	693
47.0	708	708
48.0	723	723
49.0	738	738
50.0	753	753

圧力	押側荷重	引側荷重
MPa	kN	kN
51.0	768	768
52.0	783	783
53.0	798	798
54.0	813	813
55.0	828	828
56.0	843	843
57.0	858	858
58.0	873	873
59.0	889	889
60.0	904	904
61.0	919	919
62.0	934	934
63.0	949	949
64.0	964	964
65.0	979	979
66.0	1000	1000