

圧力換算表

押引型ジャッキ
RMH100±20

能力	押 1000 kN	引 500 kN
受圧面積	押 153.90 cm ²	引 75.40 cm ²
作動圧力	押 65.00 Mpa	引 66.00 Mpa
ストローク	±200 mm	
質量	137 kg	

換算: 圧力 (MPa) × 受圧面積 (cm²) / 10 = 荷重 (kN)

圧力	押側荷重	引側荷重
MPa	kN	kN
1.0	15	8
2.0	31	15
3.0	46	23
4.0	62	30
5.0	77	38
6.0	92	45
7.0	108	53
8.0	123	60
9.0	139	68
10.0	154	75
11.0	169	83
12.0	185	90
13.0	200	98
14.0	215	106
15.0	231	113
16.0	246	121
17.0	262	128
18.0	277	136
19.0	292	143
20.0	308	151
21.0	323	158
22.0	339	166
23.0	354	173
24.0	369	181
25.0	385	189

圧力	押側荷重	引側荷重
MPa	kN	kN
26.0	400	196
27.0	416	204
28.0	431	211
29.0	446	219
30.0	462	226
31.0	477	234
32.0	492	241
33.0	508	249
34.0	523	256
35.0	539	264
36.0	554	271
37.0	569	279
38.0	585	287
39.0	600	294
40.0	616	302
41.0	631	309
42.0	646	317
43.0	662	324
44.0	677	332
45.0	693	339
46.0	708	347
47.0	723	354
48.0	739	362
49.0	754	369
50.0	770	377

圧力	押側荷重	引側荷重
MPa	kN	kN
51.0	785	385
52.0	800	392
53.0	816	400
54.0	831	407
55.0	846	415
56.0	862	422
57.0	877	430
58.0	893	437
59.0	908	445
60.0	923	452
61.0	939	460
62.0	954	467
63.0	970	475
64.0	985	483
65.0	1000	490
66.0		500