

# 圧力換算表

押引型ジャッキ  
RMH100±15

能力	押 1000 kN	引 1000 kN
受圧面積	押 364.40 cm <sup>2</sup>	引 192.40 cm <sup>2</sup>
作動圧力	押 28.00 Mpa	引 52.00 Mpa
ストローク	±150 mm	
質量	250 kg	

換算: 圧力 (MPa) × 受圧面積 (cm<sup>2</sup>) / 10 = 荷重 (kN)

圧力 MPa	押側荷重 kN	引側荷重 kN
1.0	36	19
2.0	73	38
3.0	109	58
4.0	146	77
5.0	182	96
6.0	219	115
7.0	255	135
8.0	292	154
9.0	328	173
10.0	364	192
11.0	401	212
12.0	437	231
13.0	474	250
14.0	510	269
15.0	547	289
16.0	583	308
17.0	619	327
18.0	656	346
19.0	692	366
20.0	729	385
21.0	765	404
22.0	802	423
23.0	838	443
24.0	875	462
25.0	911	481

圧力 MPa	押側荷重 kN	引側荷重 kN
26.0	947	500
27.0	984	519
28.0	1000	539
29.0		558
30.0		577
31.0		596
32.0		616
33.0		635
34.0		654
35.0		673
36.0		693
37.0		712
38.0		731
39.0		750
40.0		770
41.0		789
42.0		808
43.0		827
44.0		847
45.0		866
46.0		885
47.0		904
48.0		924
49.0		943
50.0		962

圧力 MPa	押側荷重 kN	引側荷重 kN
51.0		981
52.0		1000