

圧力換算表

押引型ジャッキ RMH100±200

能力	押 1000 kN	引 1000 kN
受圧面積	押 363.00 cm ²	引 209.10 cm ²
作動圧力	押 28.00 Mpa	引 48.00 Mpa
ストローク	±200 mm	
質量	280 kg	

換算: 圧力 (MPa) × 受圧面積 (cm²) / 10 = 荷重 (kN)

圧力	押側荷重	引側荷重
MPa	kN	kN
1.0	36	21
2.0	73	42
3.0	109	63
4.0	145	84
5.0	182	105
6.0	218	125
7.0	254	146
8.0	290	167
9.0	327	188
10.0	363	209
11.0	399	230
12.0	436	251
13.0	472	272
14.0	508	293
15.0	545	314
16.0	581	335
17.0	617	355
18.0	653	376
19.0	690	397
20.0	726	418
21.0	762	439
22.0	799	460
23.0	835	481
24.0	871	502
25.0	908	523

圧力	押側荷重	引側荷重
MPa	kN	kN
26.0	944	544
27.0	980	565
28.0	1000	585
29.0		606
30.0		627
31.0		648
32.0		669
33.0		690
34.0		711
35.0		732
36.0		753
37.0		774
38.0		795
39.0		815
40.0		836
41.0		857
42.0		878
43.0		899
44.0		920
45.0		941
46.0		962
47.0		983
48.0		1000

圧力	押側荷重	引側荷重
MPa	kN	kN