

圧力換算表

押引型ジャッキ
RMH200±15

能力	押 2000 kN	引 2000 kN
受圧面積	押 615.70 cm ²	引 301.60 cm ²
作動圧力	押 32.00 Mpa	引 66.00 Mpa
ストローク	±150 mm	
質量	540 kg	

換算: 圧力 (MPa) × 受圧面積 (cm²) / 10 = 荷重 (kN)

圧力 MPa	押側荷重 kN	引側荷重 kN
1.0	62	30
2.0	123	60
3.0	185	90
4.0	246	121
5.0	308	151
6.0	369	181
7.0	431	211
8.0	493	241
9.0	554	271
10.0	616	302
11.0	677	332
12.0	739	362
13.0	800	392
14.0	862	422
15.0	924	452
16.0	985	483
17.0	1047	513
18.0	1108	543
19.0	1170	573
20.0	1231	603
21.0	1293	633
22.0	1355	664
23.0	1416	694
24.0	1478	724
25.0	1539	754

圧力 MPa	押側荷重 kN	引側荷重 kN
26.0	1601	784
27.0	1662	814
28.0	1724	844
29.0	1786	875
30.0	1847	905
31.0	1909	935
32.0	2000	965
33.0		995
34.0		1025
35.0		1056
36.0		1086
37.0		1116
38.0		1146
39.0		1176
40.0		1206
41.0		1237
42.0		1267
43.0		1297
44.0		1327
45.0		1357
46.0		1387
47.0		1418
48.0		1448
49.0		1478
50.0		1508

圧力 MPa	押側荷重 kN	引側荷重 kN
51.0		1538
52.0		1568
53.0		1598
54.0		1629
55.0		1659
56.0		1689
57.0		1719
58.0		1749
59.0		1779
60.0		1810
61.0		1840
62.0		1870
63.0		1900
64.0		1930
65.0		1960
66.0		2000