

## 圧 力 換 算 表

押引型ジャッキ  
RMH200±20

能 力	押 2000 kN	引 2000 kN
受圧面積	押 615.70 cm <sup>2</sup>	引 361.30 cm <sup>2</sup>
作動圧力	押 32.00 Mpa	引 55.00 Mpa
ストローク	±200 mm	
質 量	600 kg	

換算：圧力 (MPa) × 受圧面積 (cm<sup>2</sup>) / 10 = 荷重 (kN)

圧 力	押側荷重	引側荷重
MPa	kN	kN
1.0	62	36
2.0	123	72
3.0	185	108
4.0	246	145
5.0	308	181
6.0	369	217
7.0	431	253
8.0	493	289
9.0	554	325
10.0	616	361
11.0	677	397
12.0	739	434
13.0	800	470
14.0	862	506
15.0	924	542
16.0	985	578
17.0	1047	614
18.0	1108	650
19.0	1170	686
20.0	1231	723
21.0	1293	759
22.0	1355	795
23.0	1416	831
24.0	1478	867
25.0	1539	903

圧 力	押側荷重	引側荷重
MPa	kN	kN
26.0	1601	939
27.0	1662	976
28.0	1724	1012
29.0	1786	1048
30.0	1847	1084
31.0	1909	1120
32.0	2000	1156
33.0		1192
34.0		1228
35.0		1265
36.0		1301
37.0		1337
38.0		1373
39.0		1409
40.0		1445
41.0		1481
42.0		1517
43.0		1554
44.0		1590
45.0		1626
46.0		1662
47.0		1698
48.0		1734
49.0		1770
50.0		1807

圧 力	押側荷重	引側荷重
MPa	kN	kN
51.0		1843
52.0		1879
53.0		1915
54.0		1951
55.0		2000