

圧力換算表

押引型ジャッキ
RMH600±20

能力	押 6000 kN	引 3000 kN
受圧面積	押 962.10 cm ²	引 471.30 cm ²
作動圧力	押 62.00 Mpa	引 64.00 Mpa
ストローク	±200 mm	
質量	940 kg	

換算: 圧力 (MPa) × 受圧面積 (cm²) / 10 = 荷重 (kN)

圧力	押側荷重	引側荷重
MPa	kN	kN
1.0	96	47
2.0	192	94
3.0	289	141
4.0	385	189
5.0	481	236
6.0	577	283
7.0	673	330
8.0	770	377
9.0	866	424
10.0	962	471
11.0	1058	518
12.0	1155	566
13.0	1251	613
14.0	1347	660
15.0	1443	707
16.0	1539	754
17.0	1636	801
18.0	1732	848
19.0	1828	895
20.0	1924	943
21.0	2020	990
22.0	2117	1037
23.0	2213	1084
24.0	2309	1131
25.0	2405	1178

圧力	押側荷重	引側荷重
MPa	kN	kN
26.0	2501	1225
27.0	2598	1273
28.0	2694	1320
29.0	2790	1367
30.0	2886	1414
31.0	2983	1461
32.0	3079	1508
33.0	3175	1555
34.0	3271	1602
35.0	3367	1650
36.0	3464	1697
37.0	3560	1744
38.0	3656	1791
39.0	3752	1838
40.0	3848	1885
41.0	3945	1932
42.0	4041	1979
43.0	4137	2027
44.0	4233	2074
45.0	4329	2121
46.0	4426	2168
47.0	4522	2215
48.0	4618	2262
49.0	4714	2309
50.0	4811	2357

圧力	押側荷重	引側荷重
MPa	kN	kN
51.0	4907	2404
52.0	5003	2451
53.0	5099	2498
54.0	5195	2545
55.0	5292	2592
56.0	5388	2639
57.0	5484	2686
58.0	5580	2734
59.0	5676	2781
60.0	5773	2828
61.0	5869	2875
62.0	6000	2922
63.0		2969
64.0		3000